

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

1 Identification of substance

- **Product details**

- **Trade name:** General Purpose Cure & Seal (J-20 UV)

- **Article number:** 83-280846

- **Application of the substance / the preparation**

- **Manufacturer/Supplier:**

Dayton Superior
4226 Kansas Avenue
Kansas City, KS 66106

Tel.: (866) 329-8724

Emergency Telephone Number: Use only in the event of an emergency involving a spill, leak, fire, exposure, or accident involving chemicals. Within the U.S., Canada, or the U.S. Virgin Islands, call ChemTrec at (800) 424-9300, 24 hours a day. Or, outside these areas, call (703) 527-3887. Collect calls are accepted.

- **Information department:** Environmental, Health, and Safety department.

2 Composition/Data on components

- **Chemical characterization**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

| | | |
|------------|--|--------|
| 8052-41-3 | Stoddard solvent | 10-25% |
| 95-63-6 | 1,2,4-trimethylbenzene | 10-25% |
| 64742-95-6 | Solvent naphtha (petroleum), light arom. | 10-25% |
| 64742-88-7 | Solvent naphtha (petroleum), medium aliph. | ≤ 2.5% |
| 25551-13-7 | Trimethylbenzene | ≤ 2.5% |
| 108-67-8 | mesitylene | ≤ 2.5% |
| 1330-20-7 | xylene | ≤ 2.5% |
| 98-82-8 | cumene | ≤ 1% |

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Hazard description:** May cause skin and eye irritation.

- **Information pertaining to particular dangers for man and environment:**

The product has to be labelled due to internationally acknowledged calculation procedures using the latest valid versions.

- **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **NFPA ratings (scale 0 - 4)**



Health = 2
Fire = 2
Reactivity = 0

(Contd. on page 2)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: General Purpose Cure & Seal (J-20 UV)

(Contd. of page 1)

· HMIS-ratings (scale 0 - 4)

| | | |
|-----------------|---|----------------|
| HEALTH | 2 | Health = *2 |
| FIRE | 2 | Fire = 2 |
| PHYSICAL HAZARD | 0 | Reactivity = 0 |

4 First aid measures

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Immediately wash with water and soap and rinse thoroughly.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. Then consult a doctor.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Seek medical treatment.

5 Fire fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:**
Water
Water with full jet
- **Protective equipment:**
Because fire may produce thermal decomposition products, wear a self-contained breathing apparatus (SCBA) with a full face piece operated in pressure-demand or positive-pressure mode.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:** Inform respective authorities in case of seepage into water course or sewage system.
- **Measures for cleaning/collecting:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Wear appropriate personal protective clothing to prevent eye and skin contact. Avoid breathing vapors or mists of this product. Use with adequate ventilation. Do not take internally.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.

(Contd. on page 3)

USA

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: **General Purpose Cure & Seal (J-20 UV)**

(Contd. of page 2)

· **Further information about storage conditions:** Keep receptacle tightly sealed.

8 Exposure controls and personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

8052-41-3 Stoddard solvent

| | |
|-----|--|
| PEL | 2900 mg/m ³ , 500 ppm |
| REL | Short-term value: C 1800* mg/m ³ Long-term value: 350 mg/m ³ *15-min |
| TLV | 525 mg/m ³ , 100 ppm |

95-63-6 1,2,4-trimethylbenzene

| | |
|-----|--------------------------------|
| REL | 125 mg/m ³ , 25 ppm |
| TLV | 123 mg/m ³ , 25 ppm |

1330-20-7 xylene

| | |
|-----|--|
| PEL | 435 mg/m ³ , 100 ppm |
| REL | Short-term value: 655 mg/m ³ , 150 ppm Long-term value: 435 mg/m ³ , 100 ppm (o-, m-, & p-isomers) |
| TLV | Short-term value: 651 mg/m ³ , 150 ppm Long-term value: 434 mg/m ³ , 100 ppm BEI |

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Personal protective equipment:**

· **General protective and hygienic measures:**

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:** Wear appropriate eye protection to prevent eye contact.

USA

(Contd. on page 4)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: **General Purpose Cure & Seal (J-20 UV)**

(Contd. of page 3)

9 Physical and chemical properties

· General Information

| | |
|---------------|------------------------------------|
| Form: | Liquid |
| Color: | According to product specification |
| Odor: | Characteristic |

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 138°C (280°F)

· **Flash point:** 41°C (106°F)

· **Ignition temperature:** 230.0°C (446°F)

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

| | |
|---------------|-----------|
| Lower: | 0.7 Vol % |
| Upper: | 7.5 Vol % |

· **Vapor pressure at 20°C (68°F):** 5.0 hPa (4 mm Hg)

· **Density at 20°C (68°F):** 0.888 g/cm³

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Solvent content:

Organic solvents: 34.1 %

· **Solids content:** 24.9 %

· **Volatile Organic Compounds:** Not determined

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

· **Dangerous reactions** No dangerous reactions known.

· **Dangerous products of decomposition:** No dangerous decomposition products known.

11 Toxicological information

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

| | | |
|------|------|-------------------|
| Oral | LD50 | >6800 mg/kg (rat) |
|------|------|-------------------|

| | | |
|--------|------|-------------------|
| Dermal | LD50 | >3400 mg/kg (rab) |
|--------|------|-------------------|

| | | |
|------------|----------|------------------|
| Inhalative | LC50/4 h | >10.2 mg/l (rat) |
|------------|----------|------------------|

95-63-6 1,2,4-trimethylbenzene

| | | |
|------|------|------------------|
| Oral | LD50 | 5000 mg/kg (rat) |
|------|------|------------------|

· Primary irritant effect:

· **on the skin:** No irritant effect.

· **on the eye:** No irritating effect.

· **Sensitization:** No sensitizing effects known.

(Contd. on page 5)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: General Purpose Cure & Seal (J-20 UV)

(Contd. of page 4)

Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Carcinogenic.

12 Ecological information

Ecotoxicological effects:

Remark: Harmful to fish

General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Harmful to aquatic organisms

13 Disposal considerations

Product:

Recommendation:

Must not be disposed of as normal garbage. Do not allow product to reach sewage system.

It is the generator's responsibility to determine if the waste meets applicable definitions of hazardous waste. State and local regulations may differ from federal disposal regulations. Dispose of waste material according to local, state, federal, and provincial environmental regulations.

Uncleaned packagings:

Recommendation: Disposal must be made according to Federal, State, and Local regulations.

14 Transport information

DOT regulations:



Hazard class:

3

Identification number:

UN1268

Packing group:

III

Proper shipping name (technical name):

PETROLEUM DISTILLATES, N.O.S.

Label

3

Remarks:

Add "Marine Pollutant" to end of proper shipping name if shipping in a bulk container (>119 gallons).

Limited Quantity Exemption:

Limited Quantity applies for inner packages 1.3 gallons or smaller.

U.S. Domestic Ground Shipments:

Combustible liquids, n.o.s. (Petroleum Distillates), NA1993, PG III

U.S. Domestic Ground Non-Bulk (119 gal or less per container) Shipments:

Not Regulated by D.O.T.

Emergency Response Guide (ERG) Number:

Not determine

Land transport ADR/RID (cross-border):



ADR/RID class:

3 Flammable liquids

(Contd. on page 6)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: General Purpose Cure & Seal (J-20 UV)

(Contd. of page 5)

· **Danger code (Kemler):** 30
 · **UN-Number:** 1268
 · **Packaging group:** III
 · **Description of goods:** 1268 PETROLEUM DISTILLATES, N.O.S.

· **Maritime transport IMDG:**

· **IMDG Class:** 3
 · **UN Number:** 1268
 · **Label:** 3
 · **Packaging group:** III
 · **EMS Number:** F-E,S-E
 · **Marine pollutant:** Yes
 · **Propper shipping name:** PETROLEUM DISTILLATES, N.O.S.

· **Air transport ICAO-TI and IATA-DGR:**

· **ICAO/IATA Class:** 3
 · **UN/ID Number:** 1268
 · **Label:** 3
 · **Packaging group:** III
 · **Propper shipping name:** PETROLEUM DISTILLATES, N.O.S.

15 Regulations

· **Sara**· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

This product may contain 1 or more toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR part 372. If so, the chemicals are listed below.

| | | |
|-----------|------------------------|--------|
| 95-63-6 | 1,2,4-trimethylbenzene | 10-25% |
| 1330-20-7 | xylene | ≤2.5% |
| 98-82-8 | cumene | ≤1% |
| 100-41-4 | ethylbenzene | ≤1% |
| 91-20-3 | naphthalene | ≤0.1% |

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**· **Chemicals known to the State of California (Prop. 65) to cause cancer:**

| | |
|------------|--|
| 64742-95-6 | Solvent naphtha (petroleum), light arom. |
| 91-20-3 | naphthalene |

(Contd. on page 7)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: General Purpose Cure & Seal (J-20 UV)

(Contd. of page 6)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Cancerogenity categories

· EPA (Environmental Protection Agency)

| | | |
|-----------|--------------|-------|
| 1330-20-7 | xylene | D |
| 98-82-8 | cumene | D;CBD |
| 100-41-4 | ethylbenzene | D |
| 91-20-3 | naphthalene | C;CBD |

· IARC (International Agency for Research on Cancer)

| | | |
|-----------|--------------|----|
| 1330-20-7 | xylene | 3 |
| 100-41-4 | ethylbenzene | 2B |
| 91-20-3 | naphthalene | 2B |

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

| | | |
|-----------|-------------|----|
| 1330-20-7 | xylene | A4 |
| 91-20-3 | naphthalene | A4 |

· MAK (German Maximum Workplace Concentration)

| | | |
|---------|-------------|---|
| 91-20-3 | naphthalene | 3 |
|---------|-------------|---|

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols: T Toxic

· Hazard-determining components of labelling:

Stoddard solvent

Solvent naphtha (petroleum), light arom.

· Risk phrases:

45 May cause cancer.

10 Flammable.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

(Contd. on page 8)

Material Safety Data Sheet

acc. to ISO/DIS 11014

Printing date 01/02/2008

Reviewed on 01/02/2008

Trade name: General Purpose Cure & Seal (J-20 UV)

(Contd. of page 7)

· Safety phrases:

- 53 Avoid exposure - obtain special instructions before use.
- 2 Keep out of the reach of children.
- 9 Keep container in a well-ventilated place.
- 13 Keep away from food, drink and animal feedingstuffs.
- 16 Keep away from sources of ignition - No smoking.
- 20 When using do not eat or drink.
- 24/25 Avoid contact with skin and eyes.
- 26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- 28 After contact with skin, wash immediately with plenty of soap and water.
- 29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
- 33 Take precautionary measures against static discharges.
- 36/39 Wear suitable protective clothing and eye/face protection.
- 43 In case of fire, use sand, carbon dioxide or powdered extinguishing agent. Never use water.
- 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
- 52 Not recommended for interior use on large surface areas.

· National regulations:

- Water hazard class:** Water hazard class 3 (Self-assessment): extremely hazardous for water.

16 Other information

The provided information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing MSDS:** Environmental, Health & Safety Department
- Contact:** Environmental, Health & Safety Manager