



Springkote

Organic, Biodegradable Form Release

Description

Springkote is an odorless, non-petroleum form release in a vegetable oil carrier. **Springkote** offers superior performance as a release for pre-cast and architectural concrete. This release is ideal for sensitive environmental situations such as bridge formwork over rivers and streams and potable water reservoirs. It utilizes the latest micro-emulsion technology to create a 100% natural, organic chemical release agent. **Springkote**, when properly applied, will provide a quick, easy and clean release of concrete from formwork. **Springkote** will not transfer to formwork and will leave concrete free of voids and defects.

Uses

Springkote can be used on various types of forms including wood, BB plyform, aluminum, plastic, fiberglass and steel. **Springkote** can be used to protect equipment such as buckets, hoists, paving machines as well as aluminum and steel windows. **Springkote** will increase the life-span of wood forms by waterproofing, protecting, cleaning and reconditioning. It will reduce maintenance on metal forms by forming a protective, rustproof film. Significant cost savings are realized with this product based on increased coverage, extended form life and reduced labor.

Benefits

- Organic: No petroleum, no odor
- Pre-blended: Ready to use
- Non-staining: Will not discolor concrete
- Performance: Waterproofs wood and rustproofs metal
- Efficient: Maximum coverage rate
- 100% Natural: Environmentally safe
- Easy application: Brush, sprayer or roller
- Long form life
- Economical: One coat coverage
- Consistent: Strict Quality Control testing and standards

Packaging: 5 gallon (18.9 L) pail
55 gallon (207.9 L) drum

Physical Properties

*Complies with National Volatile Organic Compound Emission Standards.	
COLOR	White
VISCOSITY	200 seconds
FREEZING POINT	Less than -10°F (-23°C)
FLASH POINT	Will not ignite
V.O.C	0* g/L
STAINING	None
SHELF LIFE	1 year

Standards

Springkote meets and exceed the requirements of Corps of Engineers Specification CEGS-03300, Section 10.8.

Surface Preparation

All surfaces in contact with **Springkote** shall be free of dirt, oil, grease, laitance and other contaminants that may act as bondbreakers. All rust, scale and previously used form release agents must be removed in accordance with good concrete practices. When using new forms of any type it is imperative to thoroughly saturate with **Springkote** until complete saturation has been accomplished prior to first use.

Coverage

Actual rates may vary depending on type and porosity of the surface and application methods. Recommended coverage per gallon is as follows:

Aluminum, plastic, steel	1500 ft ² /gal (36.9 m ² /L)
Medium density plywood	1250 ft ² /gal (30.8 m ² /L)
BB grade plyform	1000 ft ² /gal (24.6 m ² /L)
Dimensional lumber	1000 ft ² /gal (24.6 m ² /L)

Mixing

For best results, mix thoroughly before each use. Do not over agitate or use high speed mixing equipment.

Placing

For best results, spray application is recommended. **Springkote** may also be applied by roller coating, mopping or brushing. For maximum performance, apply a thin film to formwork. Runs or puddles should be removed with a squeegee or soft rag.

Storage

Protect from freezing. Store material in an interior, cool, dry place above 45°F (7°C). Shelf life is one year in original, unopened container.

Clean-up

Clean tools and equipment with warm, soapy water.

Limitations

In addition to the limitations already mentioned, please note the following. **Springkote** is not recommended for untreated masonite, untreated paper, aliphatic soluble form liner and form surfaces that exceed 160°F (71°C). It is not for use as a bondbreaker or concrete release agent for lift or tilt up concrete construction. Do not over apply. Over application could cause excessive surface dusting.

Regulatory

Read and follow application information, precautions and Material Safety Data Information.

HMIS

Health 1, Fire 0, Reactivity 0

VOC Content

0 g/L

Caution

Avoid contact with skin. Protective clothing is recommended. Contact areas should be thoroughly washed with soap and water. Avoid contact with eyes. Protective goggles are recommended in case of splashing. Flush eyes with water if contact occurs. Avoid ingestion of material. If ingestion occurs, contact a poison center or physician.

Technical Service

US MIX Co.
112 South Santa Fe Drive
Denver, CO 80223
Phone (303) 778-7227 Fax (303) 722-8426
Web Site: www.usspec.com

NOTICE OF LIMITED WARRANTY US MIX Co. (manufacturer) warrants to buyer that this product at the time and place of shipment is of good quality and conforms to the manufacturer's specifications in force on the date of manufacture when used in accordance with the instructions hereon. Manufacturer cannot warrant or guarantee any particular method of use, application or performance of the product under any particular condition. This limited warranty cannot be extended or amended by manufacturer's sales, people, distributors or representatives or by any sales information, specifications of anyone other than the manufacturer. Liability under this warranty is expressly limited to refund of the purchase price.
LIMITATION OF WARRANTIES AND LIABILITY Buyer assumes all risks associated with the use of this product. Manufacturer expressly disclaims all warranties expressed or implied including the warranties of merchantability and fitness for a particular purpose and all other warranties otherwise arising by operation of the law, course of dealing, custom, trade or otherwise.
Buyer's exclusive remedy if this product is proven to be defective is limited to refund of purchase price by the manufacturer. Refund shall only be available if the buyer notifies manufacturer in writing within thirty days following discovery of any defect. Written notice shall be forwarded to US MIX Co. at 112 South Santa Fe Drive, Denver, Colorado 80223. No claim can be made twelve months after purchase of the product. Twelve months after the purchase manufacturer's duties with the respect to the product and limited warranty shall be presumed to have been satisfied. Manufacturer in no event is liable for consequential damages.