



Husqvarna K 1260

Some jobs require exceptional power. The K 1260 is a real powerhouse with an impressive 7.8 hp output, turning your heaviest cutting job into a fast and effective operation. Suitable for flat work when used with the corresponding KV 970 cutting cart, which enables you to fully concentrate on the cutting job.



HIGH POWER WITH LESS FUEL

Our built-in automatic filter compensation SmartCarb™ maintains high power and lowers fuel consumption.



REDUCED WEAR

Reduced wear thanks to the drive belt with fully sealed transmission, which keeps out the cutting dust.



CUTS CLOSE TO WALLS OR GROUND

The cutting arm is reversible which lets you cut closer to walls or the ground. The drive belt has a fully sealed transmission. This keeps out cutting dust etc, reducing wear.



MAINTENANCE-FREE AIR FILTER

The only time the filter needs to be checked and changed is if you experience lack of power.

Features Husqvarna K 1260

- The drive belt with fully sealed transmission keeps out cutting dust for reduced wear and allows close cutting to walls and floor.
- Blade retarder
- Our two-step filtration system with centrifugal cleaning and a single paper filter increases product life and extends service intervals.
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.
- EasyStart ensures easier starting by reducing the compression in the cylinder.
- Our built-in automatic filter compensation maintains high power during the air filter life time.
- Provides better transmission of power, less frequent re-tensioning and extended service intervals.
- The water adjustment gives efficient dust management and makes operation easier and more efficient.

TECHNICAL SPECIFICATION	
Engine	Air-cooled 2 stroke engine
Cylinder displacement	7.25 cu.inch
Power output	7.9 hp
Fuel tank volume	42.3 fl oz
Idling speed	2700 rpm
Vibrations front handle	3.3/3.6 m/s ²
Vibrations rear handle	3.5/4.1 m/s ²
Sound pressure level at operators ear	103 dB(A)
Sound power level, guaranteed (LWA)	117 dB(A)
Blade diameter	14/16 "
Max cutting depth	5/6 "
Weight (excl. cutting equipment)	30.2/31.7 lbs

