



Husqvarna K 760

Our best-selling all-purpose power cutter is lightweight, with every detail developed with ergonomics in mind. The outstanding power-to-weight ratio and exceptionally low vibrations (below 2.5 m/s²) mean you can work longer without having to worry about vibration monitoring.



LIGHT AND POWERFUL

A light, compact and powerful machine with superior power-to-weight ratio.



EXCEPTIONALLY LOW VIBRATIONS

Vibrations below 2.5 m/s² in the cutter handles for more comfort and longer operation periods.



LONG SERVICE INTERVALS

A strong Poly-V belt combined with our maintenance-free DuraStarter™ and efficient filter-system Active Air Filtration™ ensure long service intervals.



EASY TO START

The unique design of the carburetor, cylinder and digital ignition system, together with air purge and decompression valve, ensure an easy start.

Features Husqvarna K 760

- The only time the filter needs to be checked and changed is if you experience lack of power.
- Optimized engine performance through efficient cylinder design, digital ignition system and X-Torq® engine technology.
- Easy to change bladeguard position
- High power with less fuel
- Less slurry and low water consumption
- Fits multiple blade bushings
- Our X-Torq® engine produces less emissions, has lower fuel consumption and results in more power.
- Blade retarder
- Patented, dust sealed starter unit with a sealed return spring and pulley bearing. DuraStarter™ also includes a starter cord with greatly increased durability. This makes the starter virtually maintenance free, further enhancing the reliability of our cutters.
- Reduced wear thanks to the drive belt with fully sealed transmission, which keeps out the cutting dust.
- The cutting arm is reversible which lets you cut closer to walls or the ground. The drive belt has a fully sealed transmission. This keeps out cutting dust etc, reducing wear.
- Our two-step filtration system with centrifugal cleaning and a single paper filter increases product life and extends service intervals.
- Our anti-vibration system reduces vibrations in the cutter handles, so they are more comfortable to hold and can be used for longer periods. To provide the user a comfortable operating position and to reduce strain, the distance between the handles is large. The handles and the short engine body mean the user always stands close to the machine, for easier handling and control.
- Our virtually maintenance free starter, thanks to the dust-sealed starter and the durable starter cord.
- EasyStart ensures easier starting by reducing the compression in the cylinder.
- Provides better transmission of power, less frequent re-tensioning and extended service intervals.
- Our built-in automatic filter compensation maintains high power during the air filter life time.

TECHNICAL SPECIFICATION

Engine	Air-cooled 2 stroke engine
Cylinder displacement	4.48 cu.inch
Power output	5 hp
Fuel tank volume	30.4 fl oz
Idling speed	2700 rpm
Vibrations front handle	2.4/2.4 m/s ²
Vibrations rear handle	2.4/2.4 m/s ²
Sound pressure level at operators ear	101 dB(A)
Sound power level, guaranteed (LWA)	115 dB(A)
Blade diameter	12/14"
Max cutting depth	4/5"
Weight(excl. cutting equipment)	21.2/21.6 lbs

