

Date Revised: 9/2/2015

Supersedes: 5/21/2015

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION		
Product Name(s):	Five Star Structural Concrete <sup>®</sup> Five Star Structural Concrete <sup>®</sup> V/O Five Star Structural Concrete <sup>®</sup> Gunite Five Star Structural Concrete <sup>®</sup> UW PG Five Star Structural Concrete <sup>®</sup> ES Five Star <sup>®</sup> Instant Grout	
Synonyms:	SC, IG	
Product Use:	High early strength, single component, permanent concrete repair material.	
Restrictions on Use:	N/A	
Manufacturer/Supplier	Five Star Products, Inc. 60 Parrott Drive Shelton, CT 06484 USA	
Phone #:	203-336-7900	
Emergency Phone #:	CHEM-TEL 1-800-255-3924 (Outside the U.S. 1-813-248-0585)	

## SECTION 2: HAZARD(S) IDENTIFICATION-GHS INFORMATION

Classification:	Acute Oral Toxicity – Category 4 Skin Corrosion/Irritation – Category 2 Acute Toxicity – Dermal, Category 2
	Eye Damage/Irritation – Category 1 Sensitization – Respiratory, Category 1
	Carcinogenicity – Category 1A
	Specific Target Organ Systemic Toxicity (Single Exposure) – Cat 3 Specific Target Organ Toxicity (Repeated Exposure) – Cat 2
Label Elements/Hazard Pictograms:	
Signal Word:	Danger
Hazard Statements:	Harmful if swallowed H302 May cause skin irritation H317 Causes severe skin burns and eye damage H314 May cause respiratory irritation H335 May cause an allergic skin reaction H317

FIVE STAR	Safety Data Sheet	Date Revised: 9/2/2015
~		Supersedes: 5/21/2015
	May cause cancer by inhalation H3 May cause damage to organs throu H373	
Precautionary Statements/Prevention:	Do not breathe dust, fume, gas, m Wash thoroughly after handling, P2	
	Do not eat, drink or smoke when u Contaminated work clothing should P272.	sing this product, P270. I not be allowed out of the workplace,
	Wear protective gloves, protective protection, P280.	clothing, eye protection and face
	Wear respiratory protection, P284.	
Response:	If swallowed: Rinse mouth. Do NO	T induce vomiting, P330, P331.
	If on skin (or hair): Take off immed Rinse skin with water/shower, P36	
	If inhaled: Remove person to fresh breathing, P340.	air and keep comfortable for
	If in eyes: Rinse cautiously with wa Remove contact lenses, if present a P338.	
	Immediately call a poison center or	r doctor, P310.
	If skin irritation or rash occurs, P33 P313.	33: Get medical advice/attention,
	If experiencing respiratory sympton doctor, P310. Wash contaminated of	
Storage:	Store locked up.	
Disposal:	Dispose of contents/container in ac national, and local laws and regula	
Hazards Not Otherwise Classified:	Not applicable	

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS			
Hazardous Ingredient(s)	Common Name/Synonyms	CAS No.	% wt/wt
Portland Cement	Hydraulic cement	65997-15-1	30-60
Blended Hydraulic Cement	n/a	TS	30-60
Quartz	Silicon Dioxide, Silica Sand	14808-60-7	40-60

## **SECTION 4: FIRST AID MEASURES**

Classified:



Date Revised: 9/2/2015

Supersedes: 5/21/2015

Inhalation:	If inhaled: Remove person to fresh air and keep comfortable for breathing.
Eye Contact:	If experiencing respiratory symptoms call poison center or doctor. If in eyes: Rinse cautiously with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor.
Skin Contact:	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower for at least 15 minutes. Immediately call a poison center or doctor if irritation develops. Wash contaminated clothing before reuse.
Ingestion:	If swallowed: Rinse mouth. Do NOT induce vomiting. Immediately call a poison center or doctor. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Never give anything by mouth to an unconscious person.
General Advice:	In case of accident or if you feel unwell, seek medical advice immediately (show the label or SDS where possible).
Note to Physicians:	Symptoms may not appear immediately. Treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES			
Flammability and Explosion Information:	Not flammable or combustible by OSHA/WHMIS criteria.		
Sensitivity to Mechanical Impact:	This material is not sensitive to mechanical impact.		
Sensitivity to Static Discharge:	This material is sensitive to static discharge at temperatures at or above the flash point.		
MEANS OF EXTINCTION			
Suitable Extinguishing Media:	Small Fire: Dry chemical, CO2, or water spray. Large Fire: Dry chemical, CO2, alcohol-resistant foam or water spray. Move containers from fire area if you can do it without risk. Dike fire- control water for later disposal; do not scatter the material.		
Unsuitable Extinguishing Media:	Not available		
Product of Combustion:	Non-combustible		
Protection of Firefighters:	As in any fire, wear self-contained breathing apparatus pressure- demand, MSHA/NIOSH (approved or equivalent) and full protective gear.		

SECTION 6: ACCIDENTAL RELEASE MEASURES	
Emergency Procedures:	Use personal protective equipment. Ensure adequate ventilation. Keep people from spill. Avoid dust formation.
Personal Precautions:	Avoid inhalation of dust. Do not get into eyes, on skin, or clothing.



Date Revised: 9/2/2015

Supersedes: 5/21/2015

<b>Environmental Precautions:</b>	The environmental impact of this product has not been fully investigated.
Methods for Containment:	Cover powder spill with plastic sheet or tarp to minimize spreading. Collect this material into a disposal container by sucking or sweeping up.
Methods for Cleanup:	Pick up and transfer to properly labeled containers.
Other Information:	See Section 13 for disposal considerations.

### **SECTION 7: HANDLING AND STORAGE**

Handling:	Wear personal protective equipment. Ensure adequate ventilation. Avoid dust formation. Do not breathe dust. Prevent contact with skin, eyes, and clothing. Wash thoroughly after handling.
Storage:	Keep containers tightly closed in a cool, dry, and well-ventilated place. Store locked up.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### **Exposure Guidelines**

•			
Component	CAS No.	ACGIH TLV	OSHA PEL
Portland cement	65997-15-1	TWA: 1mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction TWA: 50 mppcf <1% Crystalline silica
Blended Hydraulic Cement	TS	TWA: 1mg/m <sup>3</sup> particulate matter containing no asbestos and <1% crystalline silica, respirable fraction	TWA: 15 mg/m <sup>3</sup> total dust TWA: 5 mg/m <sup>3</sup> respirable fraction (vacated) TWA: 10 mg/m <sup>3</sup> total dust (vacated) TWA: 5 mg/m <sup>3</sup> respirable fraction TWA: 50 mppcf <1% Crystalline silica
Quartz	14808-60-7	TWA: 0.025mg/m <sup>3</sup> respirable fraction	30/(%SiO2+2) mg/m <sup>3</sup> TWA, Total Dust;250/%SiO2+5) mppcf TWA, respirable fraction; 10/(%SiO2+2) mg/m <sup>3</sup> TWA, respirable TWA: 0.1 mg/m <sup>3</sup> (vacated)

PEL: Permissible Exposure Limit TLV: Threshold Limit Value



Engineering Controls:	Not normally required.
PERSONAL PROTECTIVE EQUIP	MENT (PPE)
Eye/Face Protection:	Tightly fitting safety goggles
Hand Protection:	Impervious gloves. Impervious clothing.
Skin and Body Protection:	Impervious gloves. Impervious clothing.
Respiratory Protection:	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive- pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.
General Hygiene Considerations:	Handle according to established industrial hygiene and safety practices.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES		
Appearance:	Solid powder	
Color:	Gray, tan, brown	
Odor:	Mild	
Odor Threshold:	n/a	
Physical State:	Solid, powder	
pH:	Approximately 12 when mixed with water.	
Melting Point / Freezing Point:	n/a	
Initial Boiling Point:	n/a	
Boiling Point:	n/a	
Flash Point:	n/a	
Evaporation Rate:	n/a	
Flammability (solid, gas):	n/a	
Lower Flammability Limit:	n/a	
Upper Flammability Limit:	n/a	
Vapor Pressure:	n/a	
Vapor Density:	n/a	
Relative Density:	n/a	



Date Revised: 9/2/2015

Supersedes: 5/21/2015

Solubility:	Slight, 0.2-0.5%
Partition Coefficient: n-Octanol/Water:	n/a
Auto-ignition Temperature:	n/a
Decomposition Temperature:	n/a
Viscosity:	n/a
Percent Volatile, wt.%:	n/a
VOC Content, wt.%:	n/a
Density:	n/a
Coefficient of Water/Oil Distribution:	n/a

SECTION 10: STABILITY AND REACTIVITY			
Chemical Stability:	Stable under recommended storage conditions.		
Possibility of Hazardous Reactions:	None under normal processing.		
Conditions to Avoid:	Exposure to water – product may harden on contact with water. Manage dust formation during use.		
Incompatible Materials:	Strong acids.		

### SECTION 11: TOXICOLOGICAL INFORMATION

Information on likely routes of exposure.

Product information:	
Inhalation:	Irritating to respiratory system. Irritating to mucous membranes.
Eye contact:	Risk of serious damage to eyes.
Skin contact:	Irritating to skin. May cause allergic skin reaction
Ingestion:	Harmful if swallowed.
Component information:	

# Chemical Name: Quartz LD50 Oral: 500 mg/kg (Rat) ACGIH: A2 – Suspected Human Carcinogen IARC: Group 1 – Carcinogenic to humans OSHA: X-present

Delayed and immediate effects and also chronic effects from short and long term exposure.

SECTION 12: ECOLOGICAL INFORMATION			
Toxicity:			
Aquatic Toxicity:	The environmental impact of this product has not been fully investigated.		
Persistence and Degradability:	No information available.		
<b>Bio-accumulative Potential:</b>	Does not accumulate in organisms		



Mobility in Soil:	No further relevant information available				
Ecotoxical Effects Remark:	No information available.				
Additional Ecological Information	No information available.				
General Notes:	This statement was deduced from products with a similar structure or composition. Due to available data on eliminability/decomposition and bio-accumulation potential prolonged term damage of the environment cannot be excluded. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Also poisonous for fish and plankton in water bodies. Toxic for aquatic organisms.				
PBT Assessment:	N/A				
vPvB Assessment:	N/A				
Other Adverse Effects:	No further relevant information available				

## SECTION 13: DISPOSAL CONSIDERATIONS

Waste Treatment Methods	May be disposed of in an unrestricted sanitary landfill.
Recommendation:	This material as supplied is not a hazardous waste according to Federal regulations (40CFR261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered.
Uncleaned Packaging	
Recommendation:	Disposal must be made according to official regulations. Do not re-use empty containers.

SECTION 14: TRANSPORT INFORMATION		
US DEPARTMENT of TRANSPORTATION (DOT) Proper Shipping Name:	Not regulated.	
Class:	n/a	
UN #:	n/a	
Packing Group:	n/a	
CANADA Transportation of Dangerous Goods (TDG) Proper Shipping Name:	Not regulated.	
Class:	n/a	



UN #:	n/a
Packing Group:	n/a

### SECTION 15: REGULATORY INFORMATION

CHEMICAL INVENTORIES							
US (TSCA):	The components of this product are in compliance with the chemical notification requirements of TSCA.						
CANADA (DSL):	The components of this product are in compliance with the chemical notification requirements of NSN Regulations under CEPA, 1999.						
U.S. FEDERAL REGULATIONS	Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the CFR, Part 372.						
UNITED STATES:	This SDS has been prepared to meet the US OSHA Hazard Communication Standard, 29 CFR 1910.1200						
SARA 311/312 Hazard Categories	Acute health hazard – Yes Chronic Health hazard – Yes Fire Hazard – No Sudden Release of Pressure – No Reactive Hazard - No						
US STATE Right to Know Regulations	Chemical Name	Ŋ	MA	PA	IL	RI	
-	Portlant Cement	x	x	x		x	
					1		1

CaliforniaThis product contains the following Proposition 65 chemicals.California Prop 65:Chemical Name: Quartz CAS-No: 14808-60-7 CA Prop. 65: Carcinogen

Х

Х

Quartz

#### **SECTION 16: OTHER INFORMATION**

Disclaimer:

This information is furnished without warranty of any kind, expressed or implied. Five Star Products, Inc. bases the information and recommendations in this document on data believed to be current and accurate.

Χ

Χ